



## General

- IP 66 Weather-proof Aluminium Housing
- Side Opening Type
- Outdoor and Indoor use
- Vandal proof construction / available cable management bracket

## Spécifications / Technische Datten



Mécanique	Mechanisch	IP66 Aluminium body / Aluminium sun-shield
Poids	Gewicht	2,5 Kg
Option	Option	Blower (B), Sun Shield (S), IR Lamp
Température	Einsatztemperatur	-35°C → 50°C
Humidité	Luftfeuchte	10% → 90%
Longueur d'onde LED IR	IR LED Wellenlänge	850 nm
Angle LED	LED Winkel	20° & 45°
Portée LED IR	IR Strahler Reichweite	50 m
Dimension externe	Externe Dimension	430x142x100 mm
Dimension interne	Innenmaß	176,6x70x75 mm
Certification	Zertifizierungen	CE
Finition	Finish	Pantone Cool Gray powder coat / UV protection





## General

- One CAT-5 cable distribution signal & power
- IEEE 802.3 IBase – TX.802.3af Power over Ethernet
- In & Out Port 10/100M Auto-Negotiation RJ45 PoE (Power + DATA IN)
- Out Port : 10/100M Auto-Negotiation RJ45 PoE (Power + DATA)
- 12W and 30W (high power)

## Spécifications / Technische Datten



Terminal Layout	Pin	Input	Output
	1	Tx+ + Power2_A	
	2	Tx- + Power2_A	
	3	Rx+ + Power2_B	Rx+
	4	Power1_A	GND
	5	Power1_A	GND
	6	Rx- + Power2_B	Rx-
	7	Power1_B	+48V
	8	Power1_B	+48V



est une marque de Risk'Expert  
63, rue de Hollerich  
L 1741 Luxembourg  
Tél. : +352 26 19 02 74

L'offre globale dédiée à vos risques



[www.riskexpert.lu](http://www.riskexpert.lu)  
[contact@riskexpert.lu](mailto:contact@riskexpert.lu)



## EoC Module Series Ethernet over coax

- Simple configuration
- Save cost – Utilizing Existing Coax Cables
- Extend Transmission Distance
- Supply Power to IP Cameras through Coax/Cat5 Cables



For IP camera



Coaxial Cable  
Up to 300m



UTP  
Ethernet

Switch



## EoF Module Series Ethernet over Fiber

- Media Converters & Network Switches
- Break the 100m Barrier
- Plug-and-Play ; No configuring
- Supply Power to IP Cameras through Cat5/6 Cables



For IP camera



1 fiber



UTP  
Ethernet

Switch



1 fiber



est une marque de Risk'Expert  
63, rue de Hollerich  
L 1741 Luxembourg  
Tél. : +352 26 19 02 74

L'offre globale dédiée à vos risques



[www.riskexpert.lu](http://www.riskexpert.lu)  
[contact@riskexpert.lu](mailto:contact@riskexpert.lu)