

21.5" LED Monitor with Plastic Case

Panel Type	21.5' (16:9) LED Backlit Monitor
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	476.64 (H) x 268.11 (V) mm
Pixel Pitch	0.248 (H) x 0.248 (V) mm
Bezel Thickness	18mm
Contrast Ratio	1000:1
Brightness	250 cd/m2
Response Time	5ms
Viewing Angle	U/D: 80° / 80°, L/R: 75° / 75°
Display Colours	16.7M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9
VGA Auto Frequency correction	Yes
Speaker	Right x 1 Left x 1, 2.5W
Number of Speakers	x2
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20% - 70%
Work Temperature	-10 to 50°C
Volume +/- Power On/Off	Yes



POWER

Power Supply	12V DC, 3A
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<23W

OSD CONTROLS

Contrast, Brightness, Colour, Gamma, Colour Temperature, OSD position, OSD timeout, OSD transparency, Language, Mute, DCR, Screen size (16:9/4:3)

OSD LANGUAGE

English, German, French, Italian, Spanish, Portuguese, Russian

ACCESSORIES

Power Supply / Kettle Lead / HDMI Cable/Audio Cable / User Manual / Remote Control

IN/OUT INTERFACE

Video Interface	HDMI x1, DVI x1 , VGA x1
Audio Interface	Audio In x 1, Audio Out x 1
Power Interface	DC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS /WEEE
Vesa Standard Mount	75mm x 75mm
Stand Type	Desktop
Colour	Black
Button Position	Right Hand Side, Rear
Packing Dimension	550x419x96mm
NET Weight	3.5 Kg
GROSS Weight	4.1 Kg

