

Panel Type	24' (16:9) LED Backlit Monitor
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	531.36(H) x 298.89 (V) mm
Pixel Pitch	0.277 (H) x 0.277 (V) mm
Bezel Thickness	18mm
Contrast Ratio	1000:1
Brightness	250 cd/m2
Response Time	5ms
Viewing Angle	U/D: 80° / 80°, L/R: 75° / 75°
Display Colours	16.7M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9
VGA Auto Frequency correction	Yes
Speaker	Right x 1 Left x 1, 2.5W
Number of Speakers	x2
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20% - 70%
Work Temperature	-10 to 50°C
Volume +/- Power On/Off	Yes

IN/OUT INTERFACE

Video Interface	HDMI x1, DVI x1 , VGA x 1
Audio Interface	Audio In x 1, Audio Out x 1
Power Interface	DC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS / WEEE
Vesa Standard Mount	75mm x 75mm
Stand Type	Desktop
Colour	Black
Button Position	Right Hand Side, Rear
Packing Dimension	600x449x96mm
NET Weight	4.0 Kg
GROSS Weight	5.2 Kg



POWER

Power Supply	12V DC, 3A
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<28W

OSD CONTROLS

Contrast, Brightness, Colour, Gamma, Colour Temperature, OSD position, OSD timeout, OSD transparency, Language, Mute, DCR, Screen size (16:9/4:3)

OSD LANGUAGE

English, German, French, Italian, Spanish, Portuguese, Russian

ACCESSORIES

Power Supply / Kettle Lead / HDMI Cable/Audio Cable / User Manual / Remote Control

